

ANVIL

CLEAR COATS

JOBGING	ITEM NO	DESC.	SIZE	PK
9748-018	1550	WB Sealer	Gallon	4

**SPECIAL ORDER ONLY
FULL CASES ONLY**

CHATTAHOOCHEE STONE SEALER & GLAZE COAT WATER BASED 1550

100% Acrylic Chattahoochee Stone Sealer is a waterbased, non-yellowing clear coating for glazing and sealing exposed stone surfaces. Anvil 100% Acrylic Chattahoochee Sealer delivers a medium gloss when applied to a properly prepared surface and is highly resistant to the effects of hot automobile tires and water blushing. It is formulated for use on exterior/interior stone and concrete surfaces such as patios, walkways, decks and sidewalks. Anvil 1550 Stone Sealer is formulated to be resistant to mild automotive chemicals, oil, grease and gasoline. Its durable acrylic formula also resists fading, scuffing, cracking, peeling and blistering. Light tan color in the can but dries crystal clear.



JOBGING	ITEM NO	SIZE	PK
9701-170	2032	Quart	4
9701-171	2128	Gallon	2
REPLACED	9726-030		
	9726-031		

EnviroTex Lite® 2032 POUR-ON HIGH GLOSS FINISH

One thick coat equals up to 50 coats of varnish! A reactive polymer compound, which is solvent free, heat and alcohol resistant. It cures to a thick, glossy coating. Ideal for table and bar tops, decorative surfaces, and craft projects. EnviroTex Lite® 2032 Pour-On High Gloss Finish, 32 oz, Clear, High-Gloss, 8 sq-ft/gal Coverage, >200° F Flash



MOBILE PAINT

JOBGING	ITEM NO	SIZE	PK
63-AF-1-05	14976	5-Gal	1

MOTHANE MC-63 CLEAR FLOOR FINISH MOISTURE CURED POLYURETHANE

For industrial, commercial and residential use on wood and concrete floors. For coating properly prepared interior wood and concrete surfaces. Mothane MC-63 Clear Floor Finish offers excellent protection against abrasive traffic and spills in exposures including industrial, marine, and commercial environments. Very pale in color to minimize yellowing. Excellent chemical and abrasion resistance. Hard and flexible with good impact resistance. Lead and Chromate free. High Gloss - Clear



251-443-6110
251-408-0410 Fax

Toll Free: 1-800-621-6952
(In Alabama) 1-800-672-6707



COATINGS

ANVIL

WHITE TINT BASE			
JOBGING	ITEM NO	SIZE	PK
9748-019	922001	Gal	4
9748-020	922005	5 Gal	1
REPLACED	9748-016 9748-015		
ACCENT TINT BASE			
JOBGING	ITEM NO	SIZE	PK
9748-021	922201	Gal	4
9748-022	922205	5 Gal	1
REPLACED	9748-014 9748-011		

CONCRETE & DECKS

ANVIL® GATOR GRIP 9200 SAFE STEP

Anvil 9200 Series Gator Grip Safe-Step Coating & Bonding Primer in One has a technologically advanced formula which combines the durability of an epoxy fortified coating and primer in a single component anti-slip coating. The texture finish is 'bare foot' friendly and is easy to keep clean. Anvil Gator Grip Coating and Bonding Primer in One when applied to a properly prepared surface is highly resistant to the effects of hot automobile tires and delivers a solid color slip resistant finish. Anvil Gator Grip is formulated for use on interior and exterior painted or unpainted concrete surfaces such as garage floors, driveways, patios, walkways, decks, basements, shop floors, pool decks and sidewalks. Also, Anvil Gator Grip is formulated to be highly resistant to automotive chemicals, oil, grease and gasoline. Its' durable acrylic/epoxy/primer anti slip formula also resists fading, scuffing, cracking, peeling and blistering.



ANVIL GORILLA GRIP

Waterborne acrylic non-cementitious coating that provides an aggressive texture on surfaces where increased traction is required. Gorilla Grip's unique color adaptation properties perfectly complement Anvil Floor and Driveway Coatings by providing a decorative color match for high traction areas. It is non-flammable, low odor and is environmentally safe. Can be used as a decorative and protective coating on concrete, asphalt, wood, steel on high traction areas such as steps, floors, pool decks, patios, sidewalks, garages, carports, inclined residential driveways, safety ramps, balconies, etc. Gorilla Grip will help prevent weather deterioration of concrete while forming a unique surface texture.



JOBGING	ITEM NO	SIZE	PK
9748-007	25100010	2-Gal (10 Lb)	1
9748-008	25400040	5-Gal (40 Lb)	1

ANVIL #1750 GRIP-TITE WATERBORNE PRIMER

High Performance Waterborne Grip-Tite Bonding Primer applied directly to clean porous concrete overcomes the problem of improperly prepared surfaces prior to painting or staining. Penetrates into the concrete and improves the adhesion of the topcoat. Forms a surface that improves the workability and durability of the topcoat. Specially formulated bonding primer that can be used to improve the bonding whenever a masonry type coating. Can be used on interior/exterior, painted or unpainted, vertical/horizontal concrete, masonry, stucco, CMU block and porous brick surfaces. Also great for use as a touch up primer where other surface coatings have failed. Do not use on wood, metal, epoxy/urethane or silicone treated surfaces.



JOBGING	ITEM NO	SIZE	PK
9748-004	17500001	Gal	4

ANVIL #1720 EPOXY SHOW COAT - WHITE TINT BASE CONCRETE & GARAGE FLOOR PAINT

Combines the durability of epoxy coatings with the ease of water cleanup in a single component coating. When applied to a properly prepared surface is highly resistant to the effects of hot automobile tires and delivers a solid color satin finish and can be top coated with Anvil #2350 'Wet Look' Sealer to add a gloss finish to the surface. Formulated for use on interior and exterior painted or unpainted concrete surfaces such as garage floors, driveways, patios, walkways, decks, basements, shop floors, pool decks and sidewalks. Also, formulated to be highly resistant to automotive chemicals, oil, grease and gasoline. Its' durable acrylic/epoxy formula also resists fading, scuffing, cracking, peeling and blistering.



251-443-6110
251-408-0410 Fax

Toll Free: 1-800-621-6952
(In Alabama) 1-800-672-6707



CONCRETE & DECKS

ANVIL

JOBGING	ITEM NO	SIZE	PK
9748-006	23500001	Gal	4

ANVIL #2350 'WET LOOK' SEALER

Combines the extra durability and wet look to stained or uncoated concrete for both interior and exterior applications. Water reducible clear is non-yellowing and is low odor. When applied to a properly prepared surface is highly resistant to the effects of hot automobile tires. Anvil #2350 'Wet Look' Sealer is formulated for use on surfaces such as driveways, garage floors, patios, walkways, sidewalks, decks, pavers, un-glazed tile, brick and stucco. This product is milky white when applied, but dries to a natural super clear gloss finish. 'Wet Look' Sealer is not intended for use over wood, metal, granite, terrazzo, marble surfaces or other natural stone products.



ZINSSER

JOBGING	ITEM NO	SIZE	PK
9992-311	49104	Gal	4
9992-310	49504	4 Gal	1

RESTORE ADVANCE DECK AND CONCRETE W/ TINT BASE

This liquid-armor resurfacer forms a tough, resilient coating over existing decking. It lasts for years with minimal maintenance! Limited life-time warranty. 10 times thicker than ordinary coatings—fills cracks, locks down splinters, hides imperfections. Has a non-slip, barefoot-friendly texture. Economical and environmentally safe; and it is easy to apply and clean up. Application for wood and broom swept concrete. Base is available in 60 different colors; tint before use! Coverage rate: 25-30 sq ft per gallon with 2 coats.

JOBGING	ITEM NO	SIZE	PK
9992-321	51750	10 oz.	12

RESTORE CRACK FILLER

Restore™ coatings will fill and cover cracks up to about 1/4" in size—for imperfections larger than that, use Rust-Oleum® Restore™ Crack Filler. This textured formula evens out the surface and ensures a much smoother final result. Crack filler is for use on both wood and concrete and fills cracks up to 3/8". Coating is durable, flexible and waterproof. Coverage rate: 50 ft when bead is 3/16.



JOBGING	ITEM NO	SIZE	PK
9992-316	20114	4"	6
9992-318	RRC-9-2009	9"	6

RESTORE ROLLER COVER

- 4 roller for precise, single-board applications
- Designed specifically for deck and concrete Restore
- Disperses the product evenly across the surface leaving a uniform non slip surface



251-443-6110
251-408-0410 Fax

Toll Free: 1-800-621-6952
(In Alabama) 1-800-672-6707



COATINGS

ZINSSER/ RUST-OLEUM

GALVANIZING COMPOUND

JOBGING	ITEM	DESC.	SIZE	PK
9992-500	206193	Cold Galvanizing	Gallon	2

JOBGING	ITEM	DESC.	SIZE	PK
9992-501	206194T	Cold Galvanizing	Quart	2

7000 SYSTEM COLD GALVANIZING COMPOUND

- Self Priming & Excellent adhesion to galvanized metal.
- Two year rust-proof guarantee-maximum corrosion protection.
- Protects and Repairs Bare sheet metal, galvanized ducts, storage tanks, etc.
- Meets Federal Specifications DOD-P-21035A; MIL-P-26915C
- Meets USDA requirements for incidental food contact; accepted for use in federally registered Canadian food facilities.
- Ideal for use in mild industrial environments.

Instantly galvanize metal surfaces or repair worn or damaged galvanized steel with Rust-Oleum High Performance 7000 System Cold Galvanizing Compound. The coating contains 95% pure zinc in the dry film - for maximum corrosion resistance.



JOBGING	ITEM	DESC.	SIZE	PK
9992-480	1685830	Cold Galvanizing	14 oz.	6

JOBGING	ITEM	DESC.	SIZE	PK
9992-481	244305	Bright Galvanizing	14 oz.	6

1600 SYSTEM GALVANIZING COMPOUND SPRAY

- Touch-Up and repair galvanized ducts, storage tanks, fences, gutters, etc.
- Dries Fast - 20 minutes to touch, withstands 200°F.
- Performance offset to Federal Specifications DOD-P-21035A; MIL-P-26915C
- Meets USDA requirements for incidental food contact

Touch up galvanized surfaces with Rust-Oleum® Industrial Choice® 1600 System Galvanizing Compound Spray. This 93% pure zinc coating provides maximum corrosion resistance and excellent adhesion and durability on galvanized metal.



PRIMERS

ZINSSER/ RUST-OLEUM

JOBGING ITEM NO	SIZE	COLOR	PK
9992-011	00904	Quart White	6
9992-010	00901	Gal White	4
9870-030	01008	13 oz Spray White	6

B-I-N® SHELLAC BASE PRIMER

- Shellac-base primer-sealer
- For interior and spot exterior use
- Greatest stain sealer
- Seals knots and sap streaks
- Seals pet, smoke and musty odors
- Sticks to all surfaces without sanding
- Lightning fast dry - recoat in 45 minutes



JOBGING ITEM NO	SIZE	PK
9992-078	02241 Gal	4
9992-079	02240 5-Gal	1

BULLS EYE® WATER BASE PRIMER & SEALER INTERIOR ONLY

- Dries fast & dead flat
- Sands easily after just 1 hour
- Ultra low odor for interior work
- Great adhesion without sanding
- Easy soap & water clean up



JOBGING ITEM NO	SIZE	COLOR	PK
9992-015	03504	Quart White	6
9992-014	03501	Gal White	4
9992-086	03500	5-Gal White	1
9992-080	03610	13 oz Spray White	12

COVER STAIN® OIL BASE PRIMER INTERIOR/EXTERIOR


- Blocks cedar & redwood bleed
- Use for fire, smoke & water damage
- Sticks to all surfaces without sanding
- Fast drying - recoat in 2 hours



JOBGING ITEM NO	SIZE	PK
9992-095	276049 Gal	2
9992-096	276088 5-Gal.	1

ZINSSER® MOLD KILLING PRIMER

- Paint directly over mold
- Kills existing mold, mildew, and odor causing bacteria
- Binds chalky siding, masonry, and metal
- EPA Registered
- Interior/Exterior
- Water-Based



JOBGING ITEM NO	SIZE	COLOR	PK
9992-013	02004	Quart White	6
9992-012	02001	Gal White	4
9992-031	02000	5-Gal White	1

ZINSSER® BULLS EYE 1-2-3® WATER BASE PRIMER SEALER

- Water-base primer-sealer
- Interior and exterior
- Sticks to all surfaces without sanding
- Seals stains, graffiti and tannin bleed
- Mold & mildew resistant film
- Rust inhibitive – great for new metal
- Fast 1 hour dry time



251-443-6110 Toll Free: 1-800-621-6952
 251-408-0410 Fax (In Alabama) 1-800-672-6707



COATINGS

ZINSSER

JOBGING	ITEM NO	SIZE	PK
9992-091	249729	Gal	2

PRIMERS

SMART PRIME® PRIMER

- Oil-base performance in an advanced water-base formula
- Primer for all projects
- Sticks to all surfaces - interior and exterior
- Blocks all stains, including water stains
- Low-VOC, low odor formul



JOBGING	ITEM NO	SIZE	PK
9992-029	60001	Gal	4

PEEL STOP® CLEAR BINDING SEALER

- Interior & exterior water-base
- Extend the life of problem surfaces
- Binds cracking, chalking and peeling paint
- Glues down cracks and gaps under edges of old paint



JOBGING	ITEM NO	SIZE	PK
9992-099	11461	Gal	2

PEEL BOND XIM HIGH BUILD WATER BASED BONDING PRIMER/SEALER

- Clear high build, water based strong bonding primer, sealer and filler
- Use with Latex topcoats
- Penetrates Acrylic Latex and elastomeric paints, bonds to old paint, wood, ply wood, T1-11, PVC, Aluminum, Galvanized Metal, Brick and Stucco
- LEED Compliance
- Provides a thick wet film build on both horizontal and vertical surfaces without sagging or slipping



JOBGING	ITEM NO	SIZE	PK
9992-083	03951	Gal	4

BULLS EYE® HIGH HIDE ODORLESS PRIMER

- Interior primer-sealer and stain killer
- High-solids, low VOC specialty primer
- Performance of oil-base without the odor
- Kills water-graffiti-ink & crayon stains
- Sticks to all surfaces without sanding
- Non-yellowing, dries flat and sands easily
- VOC compliant sprayable formula
- Dries in just 30 minutes - recoat in 2 hours



251-443-6110
251-408-0410 Fax

Toll Free: 1-800-621-6952
(In Alabama) 1-800-672-6707



ANVIL

ROOF COATINGS

JOBGING	ITEM NO	SIZE	PK
9748-030	6600	5 GALLON	1

ROOF-TEC® ACRYLIC ELASTOMERIC ROOF COATING

Anvil's ROOF-TEC Acrylic Elastomeric Roof Coating is an acrylic latex roof coating formulated to provide superior bridging of the coating over seams and small separations. ROOF-TEC Acrylic exceeds performance of similar coatings of this type for adhesion and longevity. Its brilliant white finish not only beautifies, it reflects up to 90% of the sun's rays lowering heat buildup and reducing air conditioning costs. Stays brighter longer since it contains a fungicide to resist mildew growth on the product film. Do not use on flat roofs. Roofs must have an adequate pitch to allow water to run off. 10 Year Warranty



JOBGING	ITEM NO	SIZE	PK
9748-033	1220	GALLON	4

ROOF-TEC® ELASTOMERIC SMOOTH BRUSH GRADE CAULK

Anvil's #1220 ROOF-TEC Elastomeric Smooth Brush Grade Caulk is a heavy bodied, flexible, elastomeric patching material for filling and patching cracks joints and seams on: masonry, stucco, concrete block, brick stone, marble, wood, metal and glass prior to applying finish. This product provides excellent adhesion, long life and is resistant to failure by expansion, contraction, or other joint movement. Fast drying and may be painted with latex or oil base paints. For use on interior or exterior surfaces.



JOBGING	ITEM NO	SIZE	PK
9748-034	9414	4" x 100'	14

ROOF-TEC® SEAM SEALING MEMBRANE

Anvil's #9414 ROOF-TEC Seam Sealing Membrane is supplied in 100 foot rolls in widths of 4" and is designed to be used as a reinforcing material when sealing seams on roofs, flashing and around to be used as a reinforcing material when sealing seams on roofs, flashing and around protrusions when using Anvil caulking products. ROOF-TEC Polyester Membrane is more flexible than fiberglass mesh and produces a strong resilient joint and bonding system.

251-443-6110 **Toll Free: 1-800-621-6952**
251-408-0410 Fax **(In Alabama) 1-800-672-6707**



COATINGS

GEMINI

JOBGING	ITEM NO	SIZE	DESCRIPTION	PK
9736-300	TWP-100-1	Gal.	Clear	4
9736-301	TWP-100-5	5 Gal.	Clear	1
9736-302	TWP-101-1	Gal.	Cedartone	4
9736-303	TWP-101-5	5 Gal.	Cedartone	1
9736-304	TWP-102-1	Gal.	Redwood	4
9736-306	TWP-103-1	Gal.	Dark Oak	4
9736-307	TWP-103-5	5 Gal.	Dark Oak	1
9736-308	TWP-105-1	Gal.	Cape Cod Gray	4
9736-310	TWP-106-1	Gal.	Prairie Gray	4
9736-312	TWP-115-1	Gal.	Honeytone	4
9736-314	TWP-116-1	Gal.	Rustic	4
9736-315	TWP-116-5	5 Gal.	Rustic	1
9736-316	TWP-120-1	Gal.	Pecan	4

STAINS

TOTAL WOOD PRESERVATIVE 100 SERIES

TWP 100 series is an EPA registered wood preservative which prevents structural damage and wood decay on exterior above ground wood surfaces such as untreated or previously treated fencing, decking, wood siding, log homes, and roofing. It resists water absorption that causes warping, cracking and splitting as well as preventing freeze damage in colder climates. TWP 100 Series contains special U.V. absorbing pigments that prevent unsightly wood graying, darkening, and fading. The seleveted mildericides inhibit the growth of mold and mildew, which assist in preventing premature discoloration.



WATER PROOFING & WOOD PRESERVATIVES

GREEN PRODUCTS

JOBGING	ITEM NO	SIZE	PK
7400-001	30001	Gal	4

COPPER GREEN WOOD PRESERVATIVE

Copper Green Wood Preservatives eliminates all hazards of wood-eating insects and termites and it works equally well against mold, mildew, lichens, moss, and rot. When color is not an issue, copper products are the best and the most effective solution. When applying the preservative around plants, it's best to cover the plants for complete protection. However, when the preservatives dry, they are perfectly safe to use on planter boxes and greenhouses.



ZINSSER

JOBGING	ITEM NO	SIZE	COLOR	PK
9992-067	05001	Gal	White	2

WATERTITE™ MOLD & MILDEW-PROOF™ WATERPROOFING PAINT

- Great for basements and other interior/exterior concrete above and below grade masonry surfaces
- LIFETIME WATERPROOF GUARANTEE
- Guaranteed to stop up to 34 psi - twice the strength of latex waterproofer
- Prevents the growth of mold & mildew on the paint film for 5 years - guaranteed!
- Smooth, non-gritty finish applies easily to wet or dry walls
- Ultra low odor oil-base formula has less odor than latex paint



251-443-6110
251-408-0410 Fax

Toll Free: 1-800-621-6952
(In Alabama) 1-800-672-6707

