

INDUSTRIAL

PRIMERS

CODE	DESCRIPTION	SIZE
9-48	Vinyl Wash Primer	gallons
28-DR-126	Ind. Fast Dry Primer Red	5 gallons & gallon
28-DR-127	Ind. Fast Dry Red Oxide	55 gallons, 5 gallons & gallon
40-AX-7	Ind. Catalyzed MO-TAR Coal Tar	5 gallons & gallon
40-DR-5	MoPoxY HB Red Epoxy Primer	5 gallons & gallon
1000-701	Economy Shop Coat Red Oxide	50 gallons, 5 gallons & gallon
1000-801	Economy Shop Coat Gray Oxide	50 gallons, 5 gallons & gallon



CODE	DESCRIPTION	SIZE
513-4	Tinting White (with 77-13 catalyst)	5 gallons & gallon
513-10	Primer Red (with 77-13 catalyst)	5 gallons & gallon
513-11	Black (with 77-13 catalyst)	5 gallons & gallon
513-17	White (with 77-13 catalyst)	5 gallons & gallon & K4
513-18	Bone White (with 77-13 catalyst)	gallon
513-19	Egypt.Antique White(with 77-13 catalyst)	gallon
513-32	Precaution Blue (with 77-13 catalyst)	gallon
513-42	Safety Green (with 77-13 catalyst)	gallon
513-45	John Deere Green (with 77-13 catalyst)	5 gallons & gallon
513-53	Safety Yellow (with 77-13 catalyst)	gallon
513-61	Safety Orange (with 77-13 catalyst)	gallon
513-73	Tile Red (with 77-13 catalyst)	gallon
513-75	Safety Red (with 77-13 catalyst)	gallon
513-81	ANSI Gray (with 77-13 catalyst)	gallon
513-82	Dawn Gray (with 77-13 catalyst)	gallon
513-83	Battleship Gray (with 77-13 catalyst)	5 gallons & gallon
513-91	Adobe Tan (with 77-13 catalyst)	gallon
513-94	Light Beige (with 77-13 catalyst)	gallon

MOPOXY CATALYZED EPOXY COATINGS

MoPoxY™ Epoxy Coating 513-series is a two component high performance polyamide epoxy coating. Offers excellent protection in exposures including moderate to severe industrial and marine environments. Excellent resistance to fresh and salt water, detergents and most chemicals. Very good resistance to fumes and spillage of most organic solvents, acids and alkalis. Excellent abrasion and moisture resistance. Convenient 1:1 mixing ratio. Heat resistant to 200°F. Easy to apply. With MoPoxY™ Curing Agent 77-13B offers a high gloss finish. With MoPoxY™ Curing Agent 77-17B offers a semi-gloss finish. For industrial and commercial use as a protective maintenance coating for industrial plants, pulp and paper mills, textiles mills, chemical processing plants, waste water plants, refineries, food processing plants, commercial buildings and marine structures. For coating and protecting storage tanks, piping, roofs and roof decks, water towers, structural steel, machinery, plant equipment, marine vessels, offshore structures and other surfaces exposed to humidity, chemicals and corrosive environments.



251-443-6110 **Toll Free: 1-800-621-6952**
251-408-0410 Fax **(In Alabama) 1-800-672-6707**



MOBILE PAINTS

MOBILE PAINTS

INDUSTRIAL

CODE	DESCRIPTION	SIZE
72-AF-1	Exterior Clear (w/ 73-AF-4B cat.)	5 gallons & gallon
72-AG-1	Precaution Blue (w/ 73-AF-4B cat.)	5 gallons & gallon
72-AH-3	ASA#61 Gray (w/ 73-AF-4B cat.)	5 gallons & gallon
72-AM-1	International Green (w/ 73-AF-4B cat.)	5 gallons & gallon
72-AN-2	Safety Yellow (w/ 73-AF-4B cat.)	5 gallons & gallon
72-AN-9	Federal Yellow (w/ 73-AF-4B cat.)	5 gallons & gallon
72-AP-6	Aviation Safety Orange (w/ 73-AF-4B cat.)	5 gallons & gallon
72-AR-12	Safety Red (w/ 73-AF-4B cat.)	5 gallons & gallon
72-AW-1	White (w/ 73-AF-4B cat.)	5 gallons & gallon
72-AW-3	White Base (w/ 73-AF-4B cat.)	5 gallons & gallon
72-AW-4	Deep Base (w/ 73-AF-4B cat.)	5 gallons & gallon
72-AX-1	Black (w/ 73-AF-4B cat.)	5 gallons & gallon
73-AF-4B	Industrial Polyurethane Catalyst	gallon & quart
43-EF-70	Industrial Polyurethane Thinner Clear	5 gallons & gallon, qts.
43-EF-80	Industrial Mothane Retarder	5 gallons & gallon, qts.

CODE	DESCRIPTION	SIZE
520-1	Clear Tint Base	5 gallons & gallon
520-2	Deep Tint Base	5 gallons & gallon
520-4	White Tint Base	5 gallons & gallon
520-5	Primer White	5 gallons & gallon
520-8	Primer Gray	5 gallons & gallon
520-10	Primer Red	5 gallons & gallon
520-12	Flat Black	5 gallons & gallon
520-13	Gloss Black	5 gallons & gallon
520-17	White	5 gallons & gallon
520-26	Aluminum	5 gallons & gallon
520-32	Safety Blue	5 gallons & gallon
520-35	National Blue	5 gallons & gallon
520-38	Dark Blue	5 gallons & gallon
520-41	Safety Green	5 gallons & gallon
520-45	John Deere Green	5 gallons & gallon
520-48	Dark Green	5 gallons & gallon
520-55	Lead Free Safety Yellow	5 gallons & gallon
520-58	Lead Free Caterpillar Yellow	5 gallons & gallon
520-60	New Caterpillar Yellow	5 gallons & gallon
520-65	Lead Free Safety Orange	5 gallons & gallon
520-68	Brown	5 gallons & gallon
520-75	Lead Free Safety Red	5 gallons & gallon
520-81	Dawn Gray	5 gallons & gallon
520-82	ASA #61 Gray	5 gallons & gallon
520-84	Battleship Gray	5 gallons & gallon
520-92	Beige	5 gallons & gallon

MOTHANE CATALYZED POLYURETHANE ENAMELS

A two component, high performance, high gloss, aliphatic urethane coating.

MOTHANE™ Polyurethane Enamel offers excellent protection in exposures including moderate to severe industrial, commercial and marine environments. Excellent resistance to fresh and salt water, detergents and most chemicals. Very good resistance to fumes and spillage of most organic solvents, acids and alkalies. Excellent abrasion and moisture resistance. Exceptional gloss and color retention on exterior exposure. Temperature resistant to 250°.

QUICK DRY ENAMELS

A high quality quick drying, high gloss enamel for use on properly prepared ferrous metal.

For industrial and commercial use as an OEM coating for trailers, dumpsters, truck bodies and other metal equipment where a durable, easy to apply, fast dry coating is required.

Quick Dry Enamel offers excellent protection in exposures including mild industrial and marine environments. Exhibits very good adhesion to properly prepared ferrous metals. Easy to apply fast drying with good color and gloss retention.



251-443-6110 Toll Free: 1-800-621-6952
 251-408-0410 Fax (In Alabama) 1-800-672-6707



MARINE

CODE	DESCRIPTION	SIZE
431-16	Yacht White, Gloss Fume Proof	Gallon & Qts.
431-25	Yacht White, Semi-Gloss Fume Proof	Gallon & Qts.
431-46	Camouflage Ducking Skiff Olive Drab	Gallon & Qts.

JACK TAR® EXTERIOR TOPSIDE PAINTS

Jack Tar® Yacht Enamel provides protection in exposures including industrial and marine environments. A high quality, marine grade interior/exterior gloss alkyd enamel. For industrial and marine use. For painting properly prepared steel, galvanized steel, aluminum, masonry and wood surfaces. Good color and gloss retention. Excellent coverage with a high gloss, non-yellowing finish. Heat resistant up to 300°F. Lead and chromate free.

CODE	DESCRIPTION	SIZE
450-11	Black	Gallon & Qts.
450-16	White	Gallon & Qts.
450-38	Biloxi Blue	Gallon & Qts.
450-47	International Green	Gallon & Qts.
450-68	Walnut	Gallon & Qts.
450-71	International Red	Gallon & Qts.
450-74	Deck Red	Gallon & Qts.
450-83	Battleship Gray	Gallon & Qts.

JACK TAR® YACHT DECK ENAMELS

Jack Tar® Yacht Deck Enamel provides protection against weather and abrasion in industrial and marine environments. Good color and gloss retention on exterior exposure. Excellent abrasion resistance to withstand repeated traffic. Heat resistant up to 250°F.

CODE	DESCRIPTION	SIZE
492-3	Non-Skid Deck Compound	1/2 gallon & pints

JACK TAR® MISCELLANEOUS

Jack Tar® Non-Skid Deck Compound can be easily added to almost any coating to provide a durable and uniform non-skid surface. A high quality, specially selected dry pumice stone for adding non-skid properties to paint. Easily stirred into the coating. Unlike sand, this product does not settle rapidly and allows a more uniform distribution of the non-skid material in the finished coating. Uniform particle size for a better appearance. Very good abrasion resistance.

CODE	DESCRIPTION	SIZE
432-11	Black	Gallon & Qts.
432-17	White	Gallon & Qts.
432-18	Sand White	Gallon & Qts.
432-34	Perdido Blue	Gallon & Qts.
432-37	Bo'sun Blue	Gallon & Qts.
432-54	Sunshine	Gallon
432-74	Deck Red	Gallon & Qts.
432-82	Deck Gray	Gallon
432-83	Battleship Gray	Gallon & Qts.

JACK TAR® SILICONE YACHT FINISHES

Jack Tar® Silicone Yacht Finish offers excellent protection against weather and fumes in exposures including industrial and marine environments. Offers color and gloss retention and heat resistance superior to that of other alkyd coatings due to the high silicone content. Heat resistant up to 400°F. An interior and exterior, high gloss, silicone modified alkyd enamel.



251-443-6110 Toll Free: **1-800-621-6952**
251-408-0410 Fax (In Alabama) **1-800-672-6707**



MOBILE PAINTS

MOBILE PAINTS

MARINE

CODE	DESCRIPTION	SIZE
470-34	VIP-Spar Marine Spar Varnish (ultraviolet filter)	Gallon & Qts.

JACK TAR® MARINE SPAR VARNISH

Jack Tar® VIP-Spar Marine Spar Varnish with Ultraviolet Filter is a hard, high gloss, marine varnish for use where a heavy duty, tough, water repellent, mar resistant finish is desired. Formulated for marine use. Contains 100% phenolic varnishes for maximum durability and water resistance. Contains an effective ultraviolet filter to help screen out the destructive UV rays in sunlight. Easy to apply to a beautiful finish. Lead, mercury and chromate free.

RESIDENTIAL

CODE	COLOR	SIZE	PACK
64-11	Camouflage Black	gallon	4
64-48	Camouflage Olive Drab	gallon	4
64-64	Camouflage Brown	gallon	4
64-86	Camouflage Gray	gallon	4
64-92	Camouflage Tan	gallon	4

Also Available in Aerosol



ELASTOMERIC ROOF COATING

CODE	COLOR	SIZE
43-25	Reflective White	5 gal. & 1 gal.



ELASTOMERIC WALL COATING

CODE	COLOR	SIZE
43-20	White	5 gal. & 1 gal.

LATEX STAINS

CODE	COLOR	SIZE	PACK
64-68	Brown	gallon	4
64-75	Redwood	gallon	4
64-82	Weathered Cedar (Gray)	gallon	4



251-443-6110 Toll Free: 1-800-621-6952
 251-408-0410 Fax (In Alabama) 1-800-672-6707



SPECIALTY

BLP POST-LINE & BOUNDARY LINE PAINT

LEAD FREE

CODE	ITEM	SIZE
57-16	White	gallon
57-38	New Blue	gallon
57-55	Yellow	gallon
57-65	Orange	gallon
57-75	Red	gallon
22-DL-18	No Trespassing Purple Latex	gallon



BLP LUBE-60

CODE	ITEM	SIZE
10-60	Lubricant	gal., 55 gal., 12 oz. aerosol & 2 oz. aerosol



REDI-MARK TREE MARKING PAINT

LEAD FREE (Ready to Use)

CODE	ITEM	SIZE
56-36	Blue	gallon
56-56	Yellow	gallon

251-443-6110 Toll Free: 1-800-621-6952
 251-408-0410 Fax (In Alabama) 1-800-672-6707



MOBILE PAINTS

STAINS & VARNISHES

NUWOOD® SEALER & VARNISHES

CODE	DESCRIPTION	SIZE
70-1	NUWOOD® Blip Seal Wood Sealer	Gal. & Qts.
70-12	NUWOOD® Poly-Var Floor Gloss	Gal. & Qts.
70-16	NUWOOD® Poly-Var Floor Satin	Gal. & Qts.
70-23	NUWOOD® MoPaCo-Var Water Wh. Spar	Gal. & Qts.
72-35	NUWOOD® Polyurethane Gloss	Gal., Qts.
72-36	NUWOOD® Polyurethane Satin	Gal., Qts.



CODE	DESCRIPTION	SIZE
370-1	NUWOOD® H ₂ O Blip Seal Wood Sealer	Gal. & Qts.
370-12	NUWOOD® H ₂ O Poly-Var Floor Gloss	Gal. & Qts.
370-16	NUWOOD® H ₂ O Poly-Var Floor Satin	Gal. & Qts.
372-35	NUWOOD® H ₂ O Polyurethane Gloss	Gal. & Qts.
372-36	NUWOOD® H ₂ O Polyurethane Satin	Gal. & Qts.

NUWOOD® H₂O

NUWOOD® H₂O Waterborne Products are low-odor, fast drying. The varnishes apply and perform like a conventional polyurethane, but can be recoated quickly so that the job can be completed in one day. This polyurethane is a non-yellowing clear wood finish with exceptional resistance to household chemicals and abrasion. Low VOC.

CODE	DESCRIPTION	SIZE
71-1	Natural	Gal., Qts.,
71-5	Light Oak	Gal., Qts.
71-9	Golden Pine	Gal., Qts.
71-12	Early American	Gal., Qts.
71-16	Pickling White	Gal., Qts.
71-20	Provincial	Gal., Qts.
71-24	Fruitwood	Gal., Qts.
71-28	Walnut	Gal., Qts.
71-31	Dark Walnut	Gal., Qts.
71-34	Teak	Gal., Qts.,
71-36	Oriental Walnut	Gal., Qts.
71-38	Red Mahogany	Gal., Qts.,
71-2	Clear Base	Gal., Qts

NUWOOD® PENETRATING WOOD FINISHES

NUWOOD® Penetrating Wood Finish exhibits excellent penetrating and working properties on wood surfaces. Long "open" time allows even application without streaking. Uniform penetration and easy application for a beautiful, natural wood grain appearance. Lead, mercury and chromate free.

CODE	DESCRIPTION	SIZE
72-93	Oak	Gal., Qts.
72-95	Mahogany	Gal., Qts.
72-96	Walnut	Gal., Qts.,

NUWOOD® POLYURETHANE VARNISH STAIN

NUWOOD® Polyurethane Stains are tough, flexible and long wearing. Fast drying with excellent abrasion resistance. Easy to apply for staining and varnishing in one operation. Lead, mercury and chromate free.

251-443-6110 **Toll Free: 1-800-621-6952**
251-408-0410 Fax **(In Alabama) 1-800-672-6707**

