

3M

JOBGING	ITEM	SIZE	COLOR	PK.
9896-181	06500	Cartg.	White	12

MARINE ADHESIVE

- The seal is extremely strong, retains its strength above or below the water line
- Stays flexible-allows for structural movement
- Has excellent resistance to weathering and salt water



JOBGING	ITEM	SIZE	DESC.	PK.
9896-180	21200	24 oz.	Super 77	6

SUPER 77 ADHESIVE

- Fast, aggressive tack for bonding many lightweight materials
- Long bonding range with little or no soak-in



DAP INC.

JOBGING	ITEM	SIZE	COLOR	PK.
9891-273	25082	Cartg.	Tan	12

BEATS THE NAILS

- For general construction and repair projects
- Quick-grab formula provides a high-strength, heat and water resistant bond to a variety of substrates
- Meets ASTM Specification C 557
- Interior/exterior use
- 10.3 oz



FULL CASES ONLY

ELMER'S CARPENTER'S GLUE

- Professional quality aliphatic resin wood and multi-purpose glue providing a high strength bond
- Sets fast, grips tight, sands easily when dry
- Heat, water, and solvent resistant
- Non-toxic; Low VOC


JOBGING	ITEM	SIZE	PK.
9701-007	E7010	8 oz.	12
9701-008	E7020	Pint	12
9701-009	E7050	Gal	2
REPLACED	9981-264		
	9981-265		
	9981-271		



WELDWOOD ORIGINAL CONTACT CEMENT

- Premium quality, brush grade, neoprene-based contact cement that meets the stringent requirements of the professional user
- High strength and initial grab make it ideal for most projects
- Fast-drying formula dries in 15-20 minutes
- Offers high heat and water resistance when dry
- Exceeds industry performance requirements and damp conditions

JOBGING	ITEM	SIZE	PK.
9981-267	271	Pint	12
9981-268	272	Quart	6
9981-269	273	Gal	4



251-443-6110
251-408-0410 Fax

Toll Free: 1-800-621-6952
(In Alabama) 1-800-672-6707

