## ADHESIVES

A D

HES-VES

<ul> <li>3-M</li> <li>MARINE ADHESIVE</li> <li>The seal is extremely strong, retains its strength above or below the water line</li> <li>Stays flexible-allows for structural movement</li> <li>Has excellent resistance to weathering and salt water</li> </ul>	JOBBING 9896-181	ITEM N 06500	O SIZE Cartg.	COLOR White	PK 12	
SUPER 77 ADHESIVE • Fast, aggressive tack for bonding many lightweight materials • Long bonding range with little or no soak-in	JOBBING 9896-180	ITEM N 21200	O SIZE 16.75 oz	DESC . Super 77	PK 6	
DAP INC.						
BEATS THE NAILS For general construction, remodeling. Maintenance and repair products. Quick grab formula provides a high strength Heat and water resistant. Bonds to a variety of substrates. Meets ASTM C557 specifications. Interior & Exterior use. Full Cases Only	JOBBING 9981-273	ITEM N 25082	O SIZE 10.3oz. Cartg.	Color Gray	PK 12	
ELMER'S CARPENTER GLUE  • Professional quality aliphatic resin wood and multi-purpose glue providing a high strength bond  • Sets fast, grips tight, sands easily when dry  • Heat, water, and solvent resistant  • Non-toxic; Low VOC	JOBBING 9701-007		ITEM NO E7010	SIZE 8oz.	PK 12	1
	Replaced 99 9701-008	31-264	E7020	16oz.	12	
	Replaced 998 9701-009 Replaced 998		E7050	Gallon	2	ELECTRONIC DE LA CONTRACTA DE
<ul> <li>WELDWOOD ORIGINAL CONTACT CEMENT</li> <li>Premium quality, brush grade, neoprene-based contact cement that meets the stringent requirements of the professional user</li> <li>High strength and initial grab make it ideal for most projects</li> <li>Fast-drying formula dries in 15-20 minutes</li> <li>Offers high heat and water resistance when dry</li> <li>Exceeds industry performance requirements and damp conditions</li> </ul>	JOBBING 9981-267 9981-268 9981-269	ITEM N 271 272 273	O SIZE Pint Quart Gallon	PK 12 6 4		Weldwood The oreanal Contact Sec Contact

251.443.6110 251.408.0410 Fax

## Toll Free 1.800.621.6952 (In Alabama) 1.800.672.6707

3-1

BLP PAINTS